



| SEE PAGE 129 FOR UNVENTED WATER HEATER ACCESSORIES

Zip Aquapoint 3

Unvented water heater for single or multiple outlets

Features and benefits

- Sacrificial anode for protection against corrosion.
- Element 'ON' neon indicator.
- External temperature control with frost protection.
- Oversink and undersink versions available.

Capacities

5, 10 and 15 litre.

Power rating

2kW @ 230V.

Heating element

Immersion direct heat.

Thermostat

Capillary type, adjustable from 9°C to 75°C.

Water tank

Enamelled steel.

Case

High impact resistant white plastic.

Safety features

- Manually resettable over temperature safety cut-out.
- Expansion relief valve (supplied) set at 6 bar.
- Sacrificial anode gives added protection to tank, requiring regular inspection and replacement when necessary.

Insulation

High efficiency, polyurethane foam.

IP rating

IP24.

ErP rating

Class A.

Warranty

One year warranty.

Installation

- Separate models available for oversink and undersink installation.
- All models can be wall-mounted.
- Undersink systems can be installed unsupported on the floor if required.
- All models can supply one outlet or multiple outlets, subject to capacity, without the need for special taps.
- Oversink and undersink models not interchangeable.

Plumbing

Water connections 1/2 inch BSP. Expansion relief valve (supplied) set at 6 bar. Should be installed only by a suitably experienced installer of unvented electric storage water heaters.

Electrical

To be wired to a double pole switched fused spur with a minimum break capacity of 13 amps. Installation must comply with current IEE regulations. Supplied with one metre of pre-wired cable.

For general installation and specification details please visit specify.zipwater.co.uk

	Product code	Power rating kW @ 230V	Nominal capacity (litres)	ErP rating	W x D x H (mm)
Zip Aquapoint 3 Oversink	AP3/05/OB	2	6.2	A	256x260x376
	AP3/10/OB	2	9.8	A	350x265x480
	AP3/15/OB	2	14.9	A	350x310x480
Zip Aquapoint 3 Undersink	AP3/05	2	6.6	A	256x260x376
	AP3/10	2	9.9	A	350x265x480
	AP3/15	2	14.9	A	350x310x480