

floor grommets access / power and data

Dim	EG0010	The second secon		EG0040	Forth
Pack	Cat. Nos.	Plastic access grommets	Pack	Cat. Nos.	Plastic power and data grommets
		Quick fit installation			169 mm Ø – cut-out size 152 mm Ø
		Precision engineered from hard wearing durable ABS Grey mouldings. Other colours available to special order Grommets conform to IEC-61534-22 Simply secured by pushing down the spring-loaded screws and rotating a quarter turn			Quick fit installation Precision engineered from hard wearing durable ABS Grey mouldings. Other colours available to special order. Conform to IEC-61534-22 Removable carpet recess Cable flap feature so grommet lid can be closed
1	EG0010	144 mm Ø – cut-out size 127 mm Ø Can accomodate all cable types or three metal conduits up to a 20 mm Ø or 25 mm without foam			while in use Simply secured by pushing down the spring loaded screws and rotating a quarter turn
1	EG0030	169 mm Ø – cut-out size 152 mm Ø	1	EG0040	13 A power grommet Supplied complete with
		Allows power, data and flexible conduit up to 32 mm to pass through raised access floor			13 A unswitched socket
		Lid can be locked with screw (included)	1	EG0045	RCD power grommet Supplied complete with 13 A RCD socket
		Maximum number of conduits : 9 x 20 mm Ø 5 x 25 mm Ø 3 x 32 mm Ø	1	EG0051	13 A power/data grommet Supplied complete with 13 A socket and 1 x 37 x 22 mm cut-out
1	EG0055	232 mm Ø – cut-out size 215 mm Ø	1	EG0052	Data grommet Supplied complete with data plate
		High capacity grommet Recommended for installation in light traffic areas			2 x 37 x 22 mm cut-out
Pre-wired power grommets					
		Aluminium access grommet Body – cast aluminium			169 mm Ø – cut-out size 152 mm Ø
		Lid – injection moulded plastic Nylon 66 with neoprene cable gasket	4	FC0044	Cleaners socket version
		Secured by guarter-turn fasteners	1 1		DP1332 - 3 m unfused DP1532 - 5 m unfused
		Floor depth 25 to 55 mm Access grommet depth 60 mm	1 1		DP1313 - 3 m 13 A fused DP1513 - 5 m 13 A fused
1	EG0015	(95 mm when back box included) 144 mm Ø – cut-out size 127 mm Ø	·	200011	RCD socket version
1	LOUTS	Allows power, data and flexible	1		DP1332 - 3 m unfused
		conduit up to 25 mm to pass through raised access floor	1 1		DP1532 - 5 m unfused DP1313 - 3 m 13 A fused
			1		DP1513 - 5 m 13 A fused
	F00005	Aluminium power grommet			
1	EG0025	13 A power grommet Supplied complete with 13 A unswitched socket			