

Intersoc on-desk modules

with twin outlet USB charger

		Pre-wired with 3 m flex and BS 1363 plug	Pre-wired with 1.5 m flex and GST connector	Pre-wired with 1.5 m flex and Intersoc-R connector
	Description	Cat. No.	Cat. No.	Cat. No.
	1 x unfused socket plus twin outlet USB charger	PA3012AA	PB1012AA	PD1012AA
	2 x sockets individually fused at 3·15 A plus twin outlet USB charger	PA3322AA	PB1322AA	PD1322AA
	3 x sockets individually fused at 3·15 A plus twin outlet USB charger	PA3332AA	PB1332AA	PD1332AA
	1 x unfused socket, twin outlet USB charger plus 1 x rear pluggable CAT 5e / CAT 6 RJ45 outlet	PA3012AB	PB1012AB	PD1012AB
	1 x unfused socket, twin outlet USB charger plus 2 x rear pluggable CAT 5e / CAT 6 RJ45 outlets	PA3012AC	PB1012AC	PD1012AC
	1 x unfused socket, twin outlet USB charger plus 1 x rear pluggable data USB outlet	PA3012AD	PB1012AD	PD1012AD
	1 x unfused socket, twin outlet USB charger plus 2 x rear pluggable data USB outlets	PA3012AE	PB1012AE	PD1012AE
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus 1 x rear pluggable CAT 5e / CAT 6 RJ45 outlet	PA3322AB	PB1322AB	PD1322AB
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus 2 x rear pluggable CAT 5e / CAT 6 RJ45 outlets	PA3322AC	PB1322AC	PD1322AC
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus 1 x rear pluggable data USB outlet	PA3322AD	PB1322AD	PD1322AD
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus 2 x rear pluggable data USB outlets	PA3322AE	PB1322AE	PD1322AE
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus 1 x CAT 6A RJ45 outlet with 3 m data lead	PA3322AF	PB1322AF	PD1322AF
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus 2 x CAT 6A RJ45 outlets with 3 m data leads	PA3322AG	PB1322AG	PD1322AG
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus carrier to accept 1 x Euro Module (25 x 50 mm)	PA3322AK	PB1322AK	PD1322AK
	2 x sockets individually fused at 3·15 A, twin outlet USB charger plus double carrier to accept 2 x Euro Modules (50 x 50 mm)	PA3322AL	PB1322AL	PD1322AL

Notes:

Other options are available to special order. Contact us on +44 (0) 345 605 4333

CAT 5e / CAT 6 outlets have a rear facing RJ45 that will accept either CAT 5e or CAT 6 data cabling (no data cabling is included with the product)

CAT 6A outlets are supplied with 3 m pre-wired lead and performance certificate

The data USB outlets have a short flying lead at the rear for USB connection to the PC (no additional data cabling is included with the product)

Units supplied with carriers to accept Euro Modules will be supplied with apertures at the rear for the passing of data or AV cables