

TEXAS

Batten available in 4', 5' & 6' sizes
in standard and high-output



APPLICATIONS

- Suitable for commercial or domestic applications

CONSTRUCTION

- Conventional batten width steel body
- White RAL9016 powder coated finish
- Opal polycarbonate LED diffuser
- BESA fixing points on rear
- LEDs on metal core PCB
- Central cable entry point
- Piano key terminal block for speed of installation & loop in / loop out wiring
- Provided with security screws to stop removal of front cover from the body

TECHNICAL DETAILS

- 160 lm/W
- Available in 3 sizes:
 - 1x4, 24W, 2,970 lm, 126 l.lm/c.W
 - 2x4, 46W, 5,700 lm, 125 l.lm/c.W
 - 1x5, 40W, 4,760 lm, 120 l.lm/c.W
 - 2x5, 64W, 7,620 lm, 119 l.lm/c.W
 - 1x6, 49W, 6,040 lm, 124 l.lm/c.W
 - 2x6, 77W, 8,715 lm, 113 l.lm/c.W
- CRI >80
- CCT 4000K
- Branded ENEC approved flicker free driver

OPTIONS

EMERGENCY Maintained 3 hours available on all variants. Add suffix M3

TEXAS can be fitted with either of the batten-mount sensors listed on page 101, which are to be purchased separately.

| ORDER CODE | DESCRIPTION |
|---------------|------------------------------------|
| NTE1X4/840 | Texas LED Single 4Ft Batten 840 |
| NTE1X4/M3/840 | Texas LED Single 4Ft Batten M3 840 |
| NTE2X4/840 | Texas LED Twin 4Ft Batten 840 |
| NTE2X4/M3/840 | Texas LED Twin 4Ft Batten M3 840 |
| NTE1X5/840 | Texas LED Single 5Ft Batten 840 |
| NTE1X5/M3/840 | Texas LED Single 5Ft Batten M3 840 |
| NTE2X5/840 | Texas LED Twin 5Ft Batten 840 |
| NTE2X5/M3/840 | Texas LED Twin 5Ft Batten M3 840 |
| NTE1X6/840 | Texas LED Single 6Ft Batten 840 |
| NTE1X6/M3/840 | Texas LED Single 6Ft Batten M3 840 |
| NTE2X6/840 | Texas LED Twin 6Ft Batten 840 |
| NTE2X6/M3/840 | Texas LED Twin 6Ft Batten M3 840 |

